



# Product Evaluation

DR430 | 0915

Engineering Services Program

*The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).*

*This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.*

*This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.*

*For more information, contact TDI Engineering Services Program at (800) 248-6032.*

**Evaluation ID:** DR-430

**Effective Date:** September 1, 2015

**Re-evaluationDate:** September 2019

**Product Name:** 6'-8" Glazed Steel Inswing and Outswing Side Hinged Doors, Singles and Doubles, Non-Impact-Resistant, with and without Non-impact Resistant Sidelites

**Manufacturer:** Steves and Sons  
203 Humble Avenue  
San Antonio, TX 78225  
(210) 924-0470

### General Description:

System	Description	Label Rating	Drawing Number
1	3'-0" x 6'-8" Glazed Steel Single Door, Inswing / Outswing; (X)	Inswing: +30 / -35 psf Outswing: +30 / -30 psf	TX-4096
2	3'-0" x 6'-8" Glazed Steel Single Door, Inswing / Outswing w/Boxed Sidelite & Combination Reinforced Mullion; (OX / XO)	Inswing: +30 / -35 psf Outswing: +30 / -30 psf	TX-4096
3	3'-0" x 6'-8" Glazed Steel Single Door, Inswing / Outswing w/Boxed Sidelites & Combination Reinforced Mullion; (OXO)	Inswing: +30 / -35 psf Outswing: +30 / -30 psf	TX-4096
4	6'-0" x 6'-8" Glazed Steel Double Door, Inswing / Outswing; (XX)	Inswing: +30 / -35 psf Outswing: +30 / -30 psf	TX-4097
5	6'-0" x 6'-8" Glazed Steel Double Door, Inswing / Outswing w/Boxed Sidelites & Combination Reinforced Mullion; (OXXO)	Inswing: +30 / -35 psf Outswing: +30 / -30 psf	TX-4097

**Component Dimensions:**

System	Overall Size	Fixed/Operable Panel Size (Door and Sidelite)	Panel Glazed Opening Size (Door and/or Sidelite)
1	37-1/2" x 82"	35-3/4" x 79-1/2"	21" x 63"
2	54-1/2" x 82"	Door: 35-3/4" x 79-1/2" Sidelite: 14" x 79-1/2"	Door: 21" x 63" Sidelite: 5-7/8" x 63"
3	71-1/2" x 82"	Door: 35-3/4" x 79-1/2" Sidelite: 14" x 79-1/2"	Door: 21" x 63" Sidelite: 5-7/8" x 63"
4	74" x 82"	35-3/4" x 79-1/2"	21" x 63"
5	105" x 82"	Door: 35-3/4" x 79-1/2" Sidelite: 14" x 79-1/2"	Door: 21" x 63" Sidelite: 5-7/8" x 63"

**Components and Hardware:**

System	Component	Quantity	Attachment Method
1, 2, 3	4" Steel Butt Hinges	3 per door panel	Install the hardware in accordance with Steves and Sons drawing TX-4096 dated May 24, 2010 (Revised July 16, 2015), signed and sealed by Lyndon Schmidt P.E. on July 22, 2015
	Kwikset Series 200 Lock	1	
	Kwikset Series 600 Deadbolt	1	
	Latch Strike Plate	1	
	Deadbolt Strike Plate	1	

**Components and Hardware (continued):**

System	Component	Quantity	Attachment Method
4, 5	4" Steel Butt Hinges	3 per door panel	Install the hardware in accordance with Steves and Sons drawing TX-4097 dated May 24, 2010 (Revised July 16, 2015), signed and sealed by Lyndon Schmidt P.E. on July 22, 2015
	Kwikset Series 200 Lock	1	
	Kwikset Series 600 Deadbolt	1	
	Latch Strike Plate	1	
	Deadbolt Strike Plate	1	
	Astragal Strike Plate (Head)	1	
	Astragal Strike Plate (Sill)	1	

**Product Identification (Manufacturer's Label on Door):**

System		
1, 2, 3, 4, 5	Certification Agency	NAMI
	Manufacturer's Name or Code Name	Steves & Sons San Antonio, TX
	Product Name	Veranda Glazed or Opaque Steel IS or OS Side-Hinged Doors w/ or w/o Sidelites
	Test Standards	ASTM E 330-02

**Impact Resistance:**

System	Impact Resistant	Requirement
1, 2, 3, 4, 5	No	Provide an impact protective system when installing the product in areas that require windborne debris protection.

**Sidelites:** Sidelites must only be used with doors. Sidelite may not be installed individually.

**Installation:**

System		
1, 2, 3, 4, 5	Type of Installation	Install and anchor the doors on accordance with Steves and Sons drawings TX-4096 and TX-4097, dated May 24, 2010 (Revised July 16, 2015), signed and sealed by Lyndon Schmidt P.E. on July 22, 2015
	Wall Framing	
	Fasteners	
	Fastener Embedment	
	Fastener Location/Spacing	

**Note:** Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC, the IBC, and the Texas Revisions.