



Product Evaluation

RC261| 0515

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at (800) 248-6032.

Evaluation ID: RC-261

Effective Date: May 1, 2015

Reevaluation Date: May 2019

Product Name: Clay Roof Tiles

Manufacturer: Boral Roofing LLC
7575 Irvine Center Drive
Suite 100
Irvine, CA 92618
(949) 756-1605

General Description:

Boral Roofing clay roof tiles are acceptable for use in designated catastrophe areas along the Texas Gulf Coast when installed in accordance with this product evaluation report, the building specifications adopted by the TDI, and the manufacturer's installation instructions as referenced in the document entitled "Concrete and Clay Roof Tile Design Criteria Installation Manual for Moderate Climate Regions" April 2010, except for the attachment methods, which are specified in Tables 3 through 7 of this evaluation report.

Product Description:

Boral Roofing clay roof tiles are tiles that are manufactured from various clays and are kiln-fired. The tiles are available in a variety of earth tone and authentic kiln-flashed colors.

Attachment: Install the Boral Roofing clay roof tiles specified in this report using either a mechanical fastening system or an adhesive fastening system. Secure the roof tiles directly to the roof deck over the underlayment.

Roof Tile Profile Classifications: Roof tile profiles are classified as one of the following:

- **Flat/Low profile:** Flat/Low profile tiles are tiles having a rise equal to or less than 1/2".
- **Medium profile:** Medium profile tiles are defined as tiles having a rise greater than 1/2" and a rise to width ratio of less than or equal to 1.5.
- **High/Barrel profile:** High/Barrel profile tiles are those tiles having a rise to width ratio greater than 1.5.
- **Roof Tile Designations, Profile Classifications, and Dimensions:** Table 1 specifies the roof tile designations, profile classifications, and dimensions for the clay roof tiles that apply to this product evaluation report.

Table 1

Roof Tile Designations, Profile, Dimensions, Factor, and Factor Ratio

Tile Name	Alternate Name	Tile Profile	Tile				
			Length (in.)	Width		Factor (ft ³)	Factor Ratio
				Total (in.)	Exposed (in)		
ProShake® Plus	ProSlate	Flat/Low	14	8-1/2	7.7	0.663	0.472
Claylite®	Lightweight S	Medium	18	13	11	1.568	1.114
One Piece "S"	S	High	18	13	11	1.568	1.114
Tapered Two Piece Mission	Two Piece Mission	High	18	8½	8-1/2	1.211	0.861
Monterey 600	Shake, Slate	Flat/Low	13-3/4	11	10-1/2	0.8731	0.621
Monterey 700	Shake, Slate	Flat/Low	13-3/4	11	10-1/2	0.8731	0.621
Monterey 700L	Shake, Slate	Flat/Low	13-3/4	11	10-1/2	0.8731	0.621

Installation and and Limitations:

Roof Framing and Roof Deck: Install roof framing members in accordance with either the IRC or the IBC. Do not space the roof framing members greater than 24" on center. The roof deck must be solidly sheathed with minimum 15/32" plywood. Fasten the roof deck to the roof framing members in accordance with either the IRC or the IBC.

If the existing roof deck is a spaced board roof deck, then either remove or cover the spaced boards with the minimum thickness of plywood deck specified in the IRC or the IBC. Install the plywood sheathing over the spaced boards in accordance with either the IRC or the IBC.

Metal drip edge: Install a metal drip edge as specified in the manufacturer's installation instructions as referenced in the *Concrete and Clay Roof Tile Design Criteria Installation Manual for Moderate Climate Regions*.

Roof underlayment:

3:12 roof slope to under 4:12 roof slope: Two layers of underlayment complying with ASTM D 226, Type II (No. 30 asphalt felt) or equivalent. Install the underlayment as specified in either the IRC or the IBC and in the manufacturer's installation instructions as referenced in the document entitled *Concrete and Clay Roof Tile Design Criteria Installation Manual for Moderate Climate Regions*.

4:12 roof slope and greater: One layer of underlayment complying with ASTM D 226, Type I (No. 30 asphalt felt) or equivalent. Lap the underlayment a minimum of 2" at the head laps and a minimum of 6" at the side laps. Install the underlayment as specified in either the IRC or the IBC and in the manufacturer's

installation instructions as referenced in the document entitled *Concrete and Clay Roof Tile Design Criteria Installation Manual for Moderate Climate Regions*.

Self-Adhering Underlayment: Self-adhering underlayment must comply with ASTM D 1970 and ICC-ES acceptance criteria AC152 Section 3.4 Alternate Underlayments. Install the self-adhering underlayment in accordance with the self-adhering underlayment product evaluation report and the self-adhering underlayment manufacturer's installation instructions.

Battens: Install monterey roof tiles over battens. The roof deck must be solidly sheathed with minimum 15/32" plywood. Battens must be nominal 1x3 wood members. Space battens to allow for a minimum 21/4" headlap. Fasten the battens to the roof deck with minimum 8d corrosion resistant common, box or fastener with equivalent nail size. Space the nails a maximum of 24" o.c. As an alternative, the battens may be fastened to the roof deck with No. 16 gauge by 15/32" crown by 1-1/2" long staples. Space the staples a maximum of 12" o.c. Separate batten ends a minimum of 1/4" every 4' to allow for drainage.

Roof Tile Installation: Follow the limitations on mean roof height and roof slope for installing the roof tiles:

Roof Slope Limitations: Install the roof tiles on buildings with a roof slope greater than or equal to 2-1/2:12. The minimum roof slope is 3:12 unless installed on an approved waterproofing system. An installation on a roof with a roof slope greater than 7:12 requires a minimum of two fasteners per tile. When an adhesive fastening system is used, refer to the adhesive fastening system manufacturer's product evaluation for roof slope limitations.

Mean Roof Height Limitations: Table 3 through Table 7 specifies the mean roof height limitations for the mechanical attachment systems listed in these tables. Install the roof tiles on structures with a mean roof height greater than 60' when installed using these tables. For heights greater than 60' or for other attachment systems, use the procedures described in **Required Aerodynamic Uplift Moment**.

General: Install the roof tiles in accordance with this product evaluation report and the manufacturer's installation instructions. The roof tiles and the underlayment system must be clean and dry at the time of their application.

The One Piece "S" and Claylite® roof tiles must be laid out from the left to the right, starting at the left rake. The ProShake® Plus roof tiles must be laid out from the right to the left, starting at the right rake. The Tapered Two Piece Mission may be laid out either from the left or the right. Install all roof tiles with a minimum 3" headlap except the ProShake® Plus roof tiles must be installed with a minimum 2-1/4" headlap.

The Monterey roof tiles must be laid out right to left, starting at the right rake. Install Monterey roof tiles with a minimum 2-1/4" headlap. When battens are used, align the top edge or head of tile evenly with the top edge of the batten. Refer to Table 7a for direct deck installation and Table 7b for batten installation.

Install the Tapered Two Piece Mission using either a mechanical fastening system or an adhesive fastening system. The mechanical fastening system is to comply with "Mechanical Fastening Systems" except a nailer board is required for the cap tile. The nailer board must be of sufficient height so that

the nailer board and the underside of the cap tile are touching. The adhesive fastening system is to comply with the “Adhesive Fastening System”.

Required Aerodynamic Uplift Moment: The required aerodynamic uplift moment may be calculated using Section 1609.5.3 of the IBC using the length and exposed width in Table 1. The allowable resistance to required aerodynamic uplift moment is the sum of the ultimate attachment system resistance plus the restoring gravity moment from Table 2 divided by a safety factor of 2.

Table 2: Restoring Moment due to Gravity – M_g

Direct Deck Installation (ft-lbf)						
Tile	2-½:12	3:12	4:12	5:12	6:12	7:12 or Greater
ProShake® Plus	2.31	2.30	2.26	2.22	2.16	2.10
Claylite	4.73	4.69	4.60	4.48	4.35	4.21
One Piece “S”	6.42	6.38	6.25	6.10	5.93	5.74
Tapered Two Piece Mission	4.47	4.44	4.35	4.24	4.12	3.99
Monterey 600	2.90	2.88	2.84	2.78	2.71	2.63
Monterey 700	3.41	3.39	3.34	3.27	3.19	3.10
Monterey 700L	3.46	3.44	3.38	3.31	3.23	3.14

Table 3¹: Mean Roof Height Limitations

ProShake® Plus						
Gable/Hip Roof						
7° < θ ≤ 27°						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
1-#8 screw	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
2-#8 screws	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
Hip Roof						
7° < θ ≤ 25°						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
1-#8 screw	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
2-#8 screws	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
Gable Roof						
27° < θ ≤ 45°						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
1-#8 screw	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
2-#8 screws	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
Monoslope Roof						
10° < θ ≤ 30°						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
1-#8 screw	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
2-#8 screws	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}

Table 4¹: Mean Roof Height Limitations

Claylite						
Gable/Hip Roof $7^\circ < \theta \leq 27^\circ$						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ^{4,5}	30 ⁴ 60 ⁵	50 ⁴ 60 ⁵	NA ⁴ 50 ⁵	30 ^{4,5} 60 ⁵	NA ⁴ 20 ⁵
1-#8 screw	60 ^{4,5}	20 ^{4,5}	30 ^{4,5}	NA ^{4,5}	NA ^{4,5}	NA ^{4,5}
2-#8 screws	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
Hip Roof $7^\circ < \theta \leq 25^\circ$						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	50 ⁴ 60 ⁵	60 ^{4,5}	25 ⁴ 50 ⁵
1-#8 screw	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	30 ^{4,5}	60 ^{4,5}	15 ^{4,5}
2-#8 screws	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
Gable Roof $27^\circ < \theta \leq 45^\circ$						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
1-#8 screw	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	40 ^{4,5}
2-#8 screws	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
Monoslope Roof $10^\circ < \theta \leq 30^\circ$						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ^{4,5}	20 ⁴ 60 ⁵	40 ⁴ 60 ⁵	NA ⁴ 30 ⁵	NA ⁴ 60 ⁵	NA ⁴ 15 ⁵
1-#8 screw	50 ^{4,5}	NA ^{4,5}	30 ^{4,5}	NA ^{4,5}	NA ^{4,5}	NA ^{4,5}
2-#8 screws	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	40 ^{4,5}

Table 5¹: Mean Roof Height Limitations

One Piece "S"						
Gable/Hip Roof						
7° < θ ≤ 27°						
Mechanical Fastener System	Mean Roof Height Limitation²					
	Inland II		Inland I		Seaward	
	Exposure B³	Exposure C³	Exposure B³	Exposure C³	Exposure B³	Exposure C³
2-10d ring shank nails (18-22 rings per inch)	30 ⁴ 60 ⁵	NA ⁴ 60 ⁵	NA ⁴ 60 ⁵	NA ⁴ 30 ⁵	NA ⁴ 50 ⁵	NA ^{4,5}
1-#8 screw	30 ^{4,5}	NA ^{4,5}	NA ^{4,5}	NA ^{4,5}	NA ^{4,5}	NA ^{4,5}
2-#8 screws	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	40 ^{4,5}
Hip Roof						
7° < θ ≤ 25°						
Mechanical Fastener System	Mean Roof Height Limitation²					
	Inland II		Inland I		Seaward	
	Exposure B³	Exposure C³	Exposure B³	Exposure C³	Exposure B³	Exposure C³
2-10d ring shank nails (18-22 rings per inch)	60 ^{4,5}	30 ⁴ 60 ⁵	50 ⁴ 60 ⁵	NA ⁴ 60 ⁵	30 ⁴ 60 ⁵	NA ⁴ 50 ⁵
1-#8 screw	60 ^{4,5}	30 ^{4,5}	50 ^{4,5}	NA ^{4,5}	30 ^{4,5}	NA ^{4,5}
2-#8 screws	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
Gable Roof						
27° < θ ≤ 45°						
Mechanical Fastener System	Mean Roof Height Limitation²					
	Inland II		Inland I		Seaward	
	Exposure B³	Exposure C³	Exposure B³	Exposure C³	Exposure B³	Exposure C³
2-10d ring shank nails (18-22 rings per inch)	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	30 ⁴ 60 ⁵	60 ^{4,5}	15 ⁴ 60 ⁵
1-#8 screw	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	30 ^{4,5}	60 ^{4,5}	15 ^{4,5}
2-#8 screws	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
Monoslope Roof						
10° < θ ≤ 30°						
Mechanical Fastener System	Mean Roof Height Limitation²					
	Inland II		Inland I		Seaward	
	Exposure B³	Exposure C³	Exposure B³	Exposure C³	Exposure B³	Exposure C³
2-10d ring shank nails (18-22 rings per inch)	NA ⁴ 60 ⁵	NA ⁴ 40 ⁵	NA ⁴ 60 ⁵	NA ⁴ 20 ⁵	NA ⁴ 40 ⁵	NA ^{4,5}
1-#8 screw	NA ^{4,5}	NA ^{4,5}	NA ^{4,5}	NA ^{4,5}	NA ^{4,5}	NA ^{4,5}
2-#8 screws	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	30 ^{4,5}

Table 6¹: Mean Roof Height Limitations

Tapered Two Piece Mission						
Gable/Hip Roof $7^\circ < \theta \leq 27^\circ$						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ^{4,5}	25 ⁴ 60 ⁵	40 ⁴ 60 ⁵	NA ⁴ 60 ⁵	NA ⁴ 60 ⁵	NA ⁴ 40 ⁵
1-#8 screw	60 ^{4,5}	25 ^{4,5}	50 ^{4,5}	NA ^{4,5}	NA ^{4,5}	NA ^{4,5}
2-#8 screws	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
Hip Roof $7^\circ < \theta \leq 25^\circ$						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	40 ⁴ 60 ⁵	60 ^{4,5}	20 ⁴ 60 ⁵
1-#8 screw	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	40 ^{4,5}	60 ^{4,5}	20 ^{4,5}
2-#8 screws	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
Gable Roof $27^\circ < \theta \leq 45^\circ$						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	50 ⁴ 60 ⁵
1-#8 screw	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	50 ^{4,5}
2-#8 screws	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}
Monoslope Roof $10^\circ < \theta \leq 30^\circ$						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ^{4,5}	15 ⁴ 60 ⁵	30 ⁴ 60 ⁵	NA ⁴ 60 ⁵	NA ⁴ 60 ⁵	NA ⁴ 30 ⁵
1-#8 screw	60 ^{4,5}	15 ^{4,5}	30 ^{4,5}	NA ^{4,5}	NA ^{4,5}	NA ^{4,5}
2-#8 screws	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}	60 ^{4,5}

Table 7a¹: Mean Roof Height Limitations Direct Deck Installation

Monterey 600, 700 and 700L						
Gable/Hip Roof $7^\circ < \theta \leq 27^\circ$						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	40 ⁴	NA	NA	NA	NA	NA
1-#8 screw	NA	NA	NA	NA	NA	NA
2-#8 screws	60 ⁴	NA	40 ⁴	NA	NA	NA
Hip Roof $7^\circ < \theta \leq 25^\circ$						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ⁴	30 ⁴	60 ⁴	15 ⁴	30 ⁴	NA
1-#8 screw	30 ⁴	NA	NA	NA	NA	NA
2-#8 screws	60 ⁴	60 ⁴	60 ⁴	30 ⁴	60 ⁴	15 ⁴
Gable Roof $27^\circ < \theta \leq 45^\circ$						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ⁴	60 ⁴	60 ⁴	30 ⁴	60 ⁴	15 ⁴
1-#8 screw	60 ⁴	20 ⁴	40 ⁴	NA	NA	NA
2-#8 screws	60 ⁴	60 ⁴	60 ⁴	60 ⁴	60 ⁴	30 ⁴
Monoslope Roof $10^\circ < \theta \leq 30^\circ$						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	30 ⁴	NA	NA	NA	NA	NA
1-#8 screw	NA	NA	NA	NA	NA	NA
2-#8 screws	60 ⁴	15 ⁴	30 ⁴	NA	NA	NA

Table 7b¹: Mean Roof Height Limitations Batten Installation

Monterey 600, 700 and 700L						
Gable/Hip Roof $7^\circ < \theta \leq 27^\circ$						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ⁴	25 ⁴	50 ⁴	NA	30 ⁴	NA
1-#8 screw	40 ⁴	NA	NA	NA	NA	NA
2-#8 screws	50 ⁴	NA	NA	NA	NA	NA
Hip Roof $7^\circ < \theta \leq 25^\circ$						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ⁴	60 ⁴	60 ⁴	50 ⁴	60 ⁴	25 ⁴
1-#8 screw	60 ⁴	30 ⁴	60 ⁴	15 ⁴	30 ⁴	NA
2-#8 screws	60 ⁴	50 ⁴	60 ⁴	20 ⁴	40 ⁴	NA
Gable Roof $27^\circ < \theta \leq 45^\circ$						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ⁴	60 ⁴	60 ⁴	60 ⁴	60 ⁴	50 ⁴
1-#8 screw	60 ⁴	60 ⁴	60 ⁴	30 ⁴	60 ⁴	15 ⁴
2-#8 screws	60 ⁴	60 ⁴	60 ⁴	50 ⁴	60 ⁴	25 ⁴
Monoslope Roof $10^\circ < \theta \leq 30^\circ$						
Mechanical Fastener System	Mean Roof Height Limitation ²					
	Inland II		Inland I		Seaward	
	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³	Exposure B ³	Exposure C ³
2-10d ring shank nails (18-22 rings per inch)	60 ⁴	15 ⁴	30 ⁴	NA	NA	NA
1-#8 screw	30 ⁴	NA	NA	NA	NA	NA
2-#8 screws	40 ⁴	NA	NA	NA	NA	NA

Notes for Tables 3, 4, 5, 6, 7a and 7b:

1. Tables are based on an importance Factor of 1.00.
2. Mean roof height must be as defined in ASCE 7-05.
3. The Exposure category for the structure location must be as defined in ASCE 7-05.
4. Installation on a 15/32" roof deck.
5. Installation on a 19/32" roof deck.

Mechanical Fastening Systems:

Fasteners: Use fasteners for direct deck installations long enough to penetrate a minimum of 3/4" into or through the roof deck. Use fasteners for batten installations (when used) long enough to penetrate through the batten entirely and a minimum of 3/4" into or through the roof deck. The following types of fasteners may be required, depending on the installation method used as specified in ICC-ES ESR 2015P and *Concrete and Clay Roof Tile Design Criteria Installation Manual for Moderate Climate Regions*:

Screws: No. 8 steel wood screws.

Nails: 10d ring shank nails (shank diameter of 0.121").

Rake Tiles: Rake tiles must be secured to minimum Spruce-Pine-Fir lumber framing with minimum two (2) 10d box nails (3" long, 0.128" shank diameter).

Hip and Ridge Tiles: The hip and ridge tiles must be fastened to hip and ridge boards (dimensional lumber of sufficient height to support the hip and ridge tiles) in accordance with one of the following options:

- (1) Drill a 3/16" hole in the lower 1/3 of the starter tile. Use a fastener as specified in Table 8 and secure the starter tile at both the drilled hole in the lower 1/3 and at the head of the tile. Seal the head of the fastener with a UV resistant sealant.
- (2) Prior to installing the starter tile, apply a roof tile adhesive along the entire length of the starter tile. Secure the head of the starter tile with a fastener as specified in Table 8.

The remaining hip and ridge tiles are to be installed with a minimum 1" headlap. Place the toe of the tile into a 4" to 5" bead of roof tile adhesive along the head of the lower tile. The head of the hip or ridge tile is to be secured using a fastener as specified in Table 8.

Table 8
Hip and Ridge Tile Fastener Requirements

Lumber Species	Fasteners per Tile
Spruce-Pine-Fir	One No. 8 wood screw
Southern Pine	One No. 8 wood screw or One (1) 10d box nail

Adhesive Fastening Systems:

Adhesive fastening systems must comply with ICC-ES AC152, **Acceptance Criteria for Adhesive Fastening of Concrete or Clay Roof Tiles**. Refer to the adhesive fastening system manufacturer product evaluation for the allowable aerodynamic uplift moment and the installation method to develop a resistance equal to or greater than the code required aerodynamic uplift moment. Installation of roof tiles using an adhesive fastening system must be done by technicians trained and having a current certification by the adhesive fastening system manufacturer.

Adhesive fastening systems must not be used with polyethylene or silicon surfaced underlayments.

Notes: A copy of ICC-ES ESR 2015P and *Concrete and Clay Roof Tile Design Criteria Installation Manual for Moderate Climate Regions* must be available at the job site. When a self-adhering underlayment is used, the self-adhering underlayment product evaluation and the self-adhering underlayment manufacturer's installation instructions must be available at the job site. When an adhesive fastening system is used, the adhesive fastening system product evaluation and the adhesive fastening system manufacturer's installation

instructions must be available at the job site. Use corrosion resistant fasteners as specified in the IRC, the IBC, and the Texas Revisions.