



Product Evaluation

SK20 | 0515

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at (800) 248-6032.

Evaluation ID: SK-20

Effective Date: May 1, 2015

Re-evaluation Date: December 2018

Product Name: Model 750 DS Daylighting System, Impact Resistant

Manufacturer: Solatube International, Inc.
2210 Oak Ridge Way
Vista, CA 92081
(760) 597-4400

General Description:

System	Description	Label Rating	Design Pressure Rating
1	Model 750 DS Daylighting System	CW-PG70 (21") Dia – Type TDD Missile Level D	+70 / -70 psf

Product Dimensions:

System	Component	Inner Dome	Outer Dome
1	Size	22-5/8"	23-7/8"
	Height	9-1/4"	13-1/4"
	Thickness	0.168"	0.210"
	Material	Polycarbonate	Acrylic by Cyro (ZK5) or Acrylic by Arkema (DR101)
	Tube Inner Diameter	20-5/8"	

Product Identification (Certification Label on Skylight):

System		
1	Certification Agency	Keystone
	Manufacturer's Name or Code Name	CAR 110-202; CAR 110-111
	Product Name	Model 750 DS – HVHZ Daylighting System
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-08 ASTM E 1886-05, ASTM E 1996-05 Missile Level D

Impact Resistance:

System	Impact Resistant	Requirement
1	Yes	These products satisfy TDI's criteria for protection from windborne debris in the Inland I and Seaward zone. Install the assemblies at a height on the structure that does not exceed the assemblies' design pressure rating.

Installation: Secure the TDD to a minimum nominal 3/4" thick plywood roof deck. A 22-1/2" diameter hole is cut into the plywood deck. Avoid cutting roof framing members. Remove or loosen enough roof covering material along the perimeter of the roof hole to allow for the installation of the flashing. Apply a continuous 1/2" bead of roofing sealant to the underside of the flashing along the line of the screw holes. Turn the flashing upright and center over the roof hole. The metal non-pitch flashing is attached to the plywood roof deck with 16; No. 10 x 2" screws through equally spaced pre-drilled holes in the flashing. Use fasteners long enough to penetrate into and through the roof deck material. The TDD is assembled as described in this evaluation report and in the manufacturer's installation instructions.

Note: Keep the manufacturer's installation instructions at the job site during installation. Use corrosion resistant fasteners as specified in the IRC, the IBC, and the Texas Revisions.