

**Product Evaluation**

WIN2154 | 0721

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at (800) 248-6032.

**Evaluation ID:** WIN-2154**Effective Date:** July 1, 2021**Re-evaluation Date:** January 2025

**Product Name:** Premium Vinyl (V-4500) Horizontal Sliding Windows, Fin and Frame Installation, Non-Impact Resistant

**Manufacturer:** JELD-WEN Windows and Doors  
3737 Lakeport Blvd.  
Klamath Falls, OR 97601  
(541) 882-3451

**General Description:**

| System | Description  | Label Rating          | Design Pressure Rating |
|--------|--|-----------------------|------------------------|
| 1      | Premium Vinyl (V-4500) Horizontal Sliding Windows; XO  | LC-PG50 (72 x 60)-HS  | +50 / -55 psf          |
| 2      | Premium Vinyl (V-4500) Horizontal Sliding Windows; XO  | LC-PG35 (72 x 72)-HS  | +35 / -35 psf          |
| 3      | Premium Vinyl (V-4500) Horizontal Sliding Windows; XOX | LC-PG50 (96 x 60)-HS  | +50 / -55 psf          |
| 4      | Premium Vinyl (V-4500) Horizontal Sliding Windows; XOX | LC-PG35 (120 x 72)-HS | +35 / -35 psf          |

**Product Dimensions:**

| System | Overall Size | Operable Sash Size   | Fixed Sash Daylight Opening Size |
|--------|--------------|----------------------|----------------------------------|
| 1      | 71.97" x 60" | 35.04" x 57.24"      | 33.15" x 56.42"                  |
| 2      | 72" x 72"    | 35.063" x 69.25"     | 33.25" x 66.25"                  |
| 3      | 96.06" x 60" | 22.91" x 57.17" (2)  | 46.10" x 56.46"                  |
| 4      | 120" x 72"   | 38.613" x 69.25" (2) | 38.313" x 66.25"                 |

**Product Identification (Certification Label on Window):**

| System |                                  |                                 |
|--------|----------------------------------|---------------------------------|
| 1-4    | Certification Agency             | AAMA                            |
|        | Manufacturer's Name or Code Name | JW-6, JW-18                     |
|        | Product Name                     | Premium VYL (V-4500) HS         |
|        | Test Standards                   | AAMA/WDMA/CSA 101/I.S.2/A440-11 |

**Impact Resistance:**

| System | Impact Resistant | Requirement  |
|--------|------------------|--|
| 1-4    | No               | Provide an impact protective system when installing the product in areas that require windborne debris protection. |

**Installation:**

| System |                           |  |
|--------|---------------------------|--|
| 1      | Type of Installation      | Install in accordance with drawing No. SJW2015-051, dated March 25, 2021. Signed and sealed by Joseph A. Reed, P.E. on May 26, 2021. |
|        | Wall Framing              |  |
|        | Fasteners                 |  |
|        | Fastener Location/Spacing |  |
|        | Fastener Penetration      |  |
| 2      | Type of Installation      | Install in accordance with drawing No. SJW2012-040, dated April 30, 2021. Signed and sealed by Joseph A. Reed, P.E. on May 18, 2021. |
|        | Wall Framing              |  |
|        | Fasteners                 |  |
|        | Fastener Location/Spacing |  |
|        | Fastener Penetration      |  |
| 3      | Type of Installation      | Install in accordance with drawing No. D011888, dated March 31, 2021. Signed and sealed by Joseph A. Reed, P.E. on May 5, 2021.      |
|        | Wall Framing              |  |
|        | Fasteners                 |  |
|        | Fastener Location/Spacing |  |
|        | Fastener Penetration      |  |

**Installation:**

| System |                           |  |
|--------|---------------------------|--|
| 4      | Type of Installation      | Nail Fin Installation  |
|        | Wall Framing              | Southern Yellow Pine dimension lumber                        |
|        | Fasteners                 | No. 8 pan head screws  |
|        | Fastener Location/Spacing | 7-1/2" from each corner<br>and on center along the perimeter |
|        | Fastener Penetration      | Minimum of 1-1/2" into the wall framing                      |

**Note:** Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.