

PO Box 149104 | Austin, TX 78714 | 1-800-578-4677 | tdi.texas.gov

## **Product Evaluation**

#### WIN2537 | 0121

**Engineering Services Program** 

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at (800) 248-6032.

**Evaluation ID:** WIN-2537 **Effective Date:** January 1, 2021

**Re-evaluation Date:** October 2023

Product Name: Sunrise Series Vinyl Horizontal Sliding Windows, Frame Installation, Non-Impact

Resistant

Manufacturer: Sunrise Windows, LTD

200 Enterprise Dr. Temperance, MI 48182

(734) 847-8778

### **General Description:**

System	Description	Label Rating	Design Pressure Rating
1	Sunrise Series Vinyl HS Windows (XX)	LC-PG30 (72 x 56)-HS	+30 / -35 psf
2	Sunrise Series Vinyl HS Windows (XX)	LC-PG40 (63 x 44)-HS	+40 / -45 psf
3	Sunrise Series Vinyl HS Windows (XOX) 1/3-1/3-1/3	LC-PG25 (108 x 65)-HS	+25 / -25 psf
4	Sunrise Series Vinyl HS Windows (XOX) 1/3-1/3-1/3	LC-PG30 (96 x 56)-HS	+30 / -35 psf
5	Sunrise Series Vinyl HS Windows (XOX) 1/3-1/3-1/3 LC-PG40 (81 x 45)-HS +40		+40 / -45 psf
6	Sunrise Series Vinyl HS Windows (XOX) 1/4-1/2-1/4	LC-PG30 (96 x 56)-HS	+30 / -30 psf

**General Description (Continued):** 

System	Description	Label Rating	Design Pressure Rating
7	Sunrise Series Vinyl HS Windows (XOX) 1/4-1/2-1/4	LC-PG40 (81 x 45)-HS	+40 / -45 psf

## **Product Dimensions:**

System	Overall Size	Operable Sash Size	Fixed Sash Daylight Opening Size
1	72" x 56"	35-1/4" x 52-1/4" (2)	N/A
2	63" x 44"	30-3/4" x 40-1/4" (2)	N/A
3	108" x 65"	36" x 61-1/4" (2)	33-1/4" x 58-5/8"
4	96" x 56"	32" x 52-1/4" (2)	29-3/8" x 49-5/8"
5	81" x 45"	27" x 41-1/4" (2)	24-1/4" x 38-3/8"
6	96" x 56"	24" x 52-1/4" (2)	45-3/8" x 49-9/16"
7	81" x 45"	20-1/4" x 41-1/4" (2)	37-7/8" x 38-5/8"

## **Product Identification (Certification Label on Window):**

Systen	1	
	Certification Agency	NAMI
1-7	Manufacturer's Name or Code Name	Sunrise Windows & Doors
1-7	Product Name	Vinyl Horizontal Sliding Window
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11

**Impact Resistance:** 

System	Impact Resistant	Requirement
1-7	No	Provide an impact protective system when installing the product in areas that require windborne debris protection.

**Acceptance of Smaller Assemblies:** Window assemblies with dimensions equal to or smaller than those specified are acceptable within the limitations of this report.

### Installation:

System		
	Type of Installation Wall Framing	Install in accordance with Sunrise Windows &
1-2	Fasteners	Doors drawing No. TX-5021, dated April 13, 2020.
	Fastener Location/Spacing	Signed and sealed by Lyndon F. Schmidt, P.E. on April 15, 2020.
	Fastener Penetration	Αβιίι 13, 2020.

# **Installation (Continued):**

System		
3-7	Type of Installation Wall Framing Fasteners Fastener Location/Spacing Fastener Penetration	Install in accordance with Sunrise Windows & Doors drawing No. TX-5051 and TX-5052, dated May 6, 2020. Signed and sealed by Lyndon F. Schmidt, P.E. on June 30, 2020.

**Note:** Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.