

PO Box 149104 | Austin, TX 78714 | 1-800-578-4677 | tdi.texas.gov

Product Evaluation

WIN2563 | 0221

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at (800) 248-6032.

Evaluation ID: WIN-2563

Effective Date:February 1, 2021Re-evaluation Date:June 2023

Product Name: Inspira Vinyl Horizontal Slider Windows, Fin and Frame Installation, Non-Impact Resistant

Manufacturer: Northeast Building Products 4280 Aramingo Philadelphia, PA 19124 (215) 535-7110

General Description:

System	Description	Label Rating	Design Pressure Rating
1	Inspira New Construction Vinyl Horizontal Slider Windows; XX 2SL	Class LC-PG25 71 x 56 Type HS	±25 psf
2	Inspira Replacement Vinyl Horizontal Slider Windows; XX; 2SL	Class LC-PG35 71 x 56 Type HS	±35 psf
3	Inspira New Construction Vinyl Horizontal Slider Windows; XX; 2SL	Class LC-PG40 63 x 44 Type HS	±40 psf

General Description (Continued):

General Description (Continued):			
System	Description	Label Rating	Design Pressure Rating
4	Inspira Replacement Vinyl Horizontal Slider Windows; XX; 2SL	Class LC-PG45 63 x 44 Type HS	+45; -50 psf
5	Inspira Replacement Vinyl Horizontal Slider Windows; XOX; 3SL	Class LC-PG25 109 x 66 Type HS	±25 psf
6	Inspira Replacement Vinyl Horizontal Slider Windows; XOX; 3SL	Class LC-PG25 93 x 66 Type HS	±25 psf
7	Inspira Construction Vinyl Horizontal Slider Windows; XOX 3SL	Class LC-PG35 93 x 44 Type HS	±35 psf
8	Inspira Replacement Vinyl Horizontal Slider Windows; XOX; 3SL	Class LC-PG40 93 x 44 Type HS	±40 psf
9	Inspira Replacement Vinyl Horizontal Slider Windows; QHQ; XOX	Class LC-PG25 93 x 66 Type HS	±25 psf
10	Inspira New Construction Vinyl Horizontal Slider Windows; QHQ; XOX	Class LC-PG35 93 x 44 Type HS	±35 psf
11	Inspira Replacement Vinyl Horizontal Slider Windows; QHQ; XOX	Class LC-PG40 93 x 44 Type HS	±40 psf

Product Dimensions:

System	Overall Size	Operable Sash Size	Fixed Sash Size
1, 2	71" x 56"	34-13/16" x 52-1/4"	N/A
3, 4	63" x 44"	30-5/8" x 40-1/4"	N/A
5	109" x 66"	33-5/16" x 62-1/4"	33-5/16" x 62-1/4"
6	93" x 66"	30-7/8" x 62-3/16"	30-7/8" x 62-3/16"
7, 8	93" x 44"	30-7/8" x 40-3/16"	30-7/8" x 40-3/16"
9	93" x 66"	23-3/16" x 62-1/4"	46-1/8" x 62-1/4"
10, 11	93" x 44"	23-3/16" x 40-3/16"	46-1/8" x 40-3/16"

Product Identification (Certification Label on Window):

System		
	Certification Agency	Keystone
1	Manufacturer's Name or Code Name	86-448
	Product Name	Crusader Elite SL / Inspira SL Horizontal Sliding Window (XX) N/C
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11
	Certification Agency	Keystone
	Manufacturer's Name or Code Name	86-449
2	Product Name	Crusader Elite SL / Inspira SL Horizontal Sliding Window (XX) Repl
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11
	Certification Agency	Keystone
	Manufacturer's Name or Code Name	86-450
3	Product Name	Crusader Elite SL / Inspira SL Horizontal Sliding Window (XX) N/C
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11
	Certification Agency	Keystone
	Manufacturer's Name or Code Name	86-451
4	Product Name	Crusader Elite SL / Inspira SL Horizontal Sliding Window (XX) Repl
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11
	Certification Agency	Keystone
	Manufacturer's Name or Code Name	86-473
5	Product Name	Crusader Elite SL / Inspira SL PVC HS (1/3-1/3- 1/3) Repl
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11
	Certification Agency	Keystone
	Manufacturer's Name or Code Name	86-475
6	Product Name	Crusader Elite SL / Inspira SL PVC HS (1/3-1/3- 1/3) Repl
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11
	Certification Agency	Keystone
	Manufacturer's Name or Code Name	86-476
7	Product Name	Crusader Elite SL / Inspira SL PVC HS (1/3-1/3- 1/3) NC
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11
	Certification Agency	Keystone
	Manufacturer's Name or Code Name	86-477
8	Product Name	Crusader Elite SL / Inspira SL PVC HS (1/3-1/3- 1/3) Repl
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11

System		
	Certification Agency	Keystone
	Manufacturer's Name or Code Name	86-480
9	Product Name	Crusader Elite SL / Inspira SL PVC HS
		(1/4-1/2-1/4) Repl
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11
	Certification Agency	Keystone
	Manufacturer's Name or Code Name	86-481
10	Product Name	Crusader Elite SL / Inspira SL PVC HS
		(1/4-1/2-1/4) NC
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11
	Certification Agency	Keystone
	Manufacturer's Name or Code Name	86-482
11	Product Name	Crusader Elite SL / Inspira SL PVC HS
		(1/4-1/2-1/4) Repl
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11

Product Identification (Certification Label on Window) - continued:

Impact Resistance:

System	Impact Resistant	Requirement
1-11	No	Provide an impact protective system when installing the product in areas that require windborne debris.

Installation:

System		
	Type of Installation	Install the windows in accordance with Drawing
	Wall Framing	TDI-INSPIRA-HS-NI; sheets 1 through 4 of 4;
1-11	Fasteners	dated February 10, 2020; Revision 0; Signed,
	Fastener Location/Spacing	sealed, and dated November 12, 2020 by Lucas
	Fastener Penetration	A. Turner, P.E.

Note: Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.