

PO Box 12030 | Austin, TX 78711 | 800-578-4677 | tdi.texas.gov

Product Evaluation

WIN760 | 0122

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at (800) 248-6032.

Evaluation ID: WIN-760 **Effective Date:** January 1, 2022

Re-evaluation Date: January 2026

Product Name: Premium Atlantic Vinyl Horizontal Sliding Windows, Fin and Frame Installation,

Impact Resistant

Manufacturer: JELD-WEN Windows and Doors

3737 Lakeport Boulevard Klamath Falls, OR 97601

(541) 882-3451

General Description:

System	Description	Label Rating	Design Pressure Rating
1	Premium Atlantic Vinyl Horizontal	R-PG50 (74 x 54)-HS	+50 / -55 psf
I	Sliding Windows	Missile Level D	+50 / -55 psi
2	Premium Atlantic Vinyl Horizontal	R-PG60 (74 x 54)-HS	160 / 65 pcf
	Sliding Windows	Missile Level D	+60 / -65 psf
3	Premium Atlantic Vinyl Horizontal	LC-PG50 (74 x 62)-HS	150 / 50 pcf
	Sliding Windows	Missile Level D	+50 / -50 psf
4	Premium Atlantic Vinyl Horizontal	LC-PG50 (74 x 62)-HS	LEO / EE pef
	Sliding Windows	Missile Level D	+50 / -55 psf

Product Dimensions:

System	Overall Size	Operable Sash Size	Fixed Sash Daylight Opening Size
1-2	74" x 54"	37" x 51-1/4"	33-5/8" x 50-1/2"
3-4	74" x 62"	37" x 59-1/4"	33-5/8" x 58-1/2"

Product Identification (Certification Label on Window):

System		
	Certification Agency	WDMA
Manufacturer's Name or Code Nam		JW-19
1-4	Product Name	PAV HS
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11
		AAMA 506; Missile Level D

Impact Resistance:

System	Impact Resistant	Requirement
1-4	Yes	These products satisfy TDI's criteria for protection from windborne debris. Install the assemblies at a height on the structure that does not exceed the design pressure rating for the assemblies.

Installation:

System			
1	Type of Installation	Install in accordance with drawing with report No NCTL-210-3896-1A, dated October 12, 2021. Signed and sealed by Joseph A. Reed, P.E. on October 20, 2021.	
	Wall Framing		
	Fasteners		
	Fastener Location/Spacing		
	Fastener Penetration		
2	Type of Installation	Install in accordance with drawing with report No NCTL-210-3897-1A, dated October 12, 2021. Signed and sealed by Joseph A. Reed, P.E. on October 20, 2021.	
	Wall Framing		
	Fasteners		
	Fastener Location/Spacing		
	Fastener Penetration		
	Type of Installation	Install in accordance with drawing with report N NCTL-210-3894-1A, dated October 12, 2021. Signed and sealed by Joseph A. Reed, P.E. on October 20, 2021.	
3	Wall Framing		
	Fasteners		
	Fastener Location/Spacing		
	Fastener Penetration		

Installation:

System		
	Type of Installation	Land III to a considerate the first transfer of Nicoland
	Wall Framing	Install in accordance with drawing with report No.
4	Fasteners	NCTL-210-3895-1A, dated October 12, 2021. Signed and sealed by Joseph A. Reed, P.E. on
	Fastener Location/Spacing	October 20, 2021.
	Fastener Penetration	October 20, 2021.

Note: Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.