

## Product Evaluation

DR1155 | 0521

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at 800-248-6032.

**Evaluation ID:** DR-1155

**Effective Date:** May 1, 2021

**Re-evaluation Date:** May 2025

**Product Name:** SLPS Glazed Fiberglass Sliding Glass Patio Doors, Frame Installation, Impact Resistant

**Manufacturer:** Nan Ya Plastics Corporation USA  
8989 North Loop East  
Houston, Texas 77029  
(713) 674-7822

### General Description:

System	Description	Label Rating	Design Pressure Rating
1	SLPS Glazed Fiberglass Sliding Patio Doors; OXXO	R-PG50 (141 x 96)-SD Missile Level D	+50 / -50 psf

### Product Dimensions:

System	Overall size	Operable Panel Size	Panel Daylight Opening Size
1	141-1/8" x 95-1/2"	35-3/4" x 92-3/8"	25" x 79"

**Product Identification (Certification Label on Door):**

System		
1	Certification agency	NAMI
	Manufacturer's name or code name	Nan Ya Plastics USA
	Product name	SLPS Glazed Impact Rated Fiberglass Gliding Patio Door
	Test standards	AAMA/WDMA/CSA 101/I.S.2/A440-011 ASTM E1886-05/E1996-05,09 Missile Level D

**Impact Resistance:**

System	Impact Resistant	Requirement
1	Yes	These products satisfy TDI's criteria for protection from windborne debris. Install the assemblies at a height on the structure that does not exceed the design pressure rating for the assemblies.

**Installation:**

System		
1	Type of installation	Install in accordance with Nan Ya Plastics drawing No. 08-03631, dated October 21, 2020. Signed and sealed by Luis R. Lomas, P.E. on April 21, 2021.
	Wall framing	
	Fasteners	
	Fastener location/spacing	
	Fastener penetration	

**Note:** Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.