

Product Evaluation

WIN2561 | 0221

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at (800) 248-6032.

Evaluation ID: WIN-2561

Effective Date: February 1, 2021

Re-evaluation Date: February 2024

Product Name: Inspira Vinyl Casement Windows, Fin and Frame Installation, Non-Impact Resistant

Manufacturer: Northeast Building Products
4280 Aramingo
Philadelphia, PA 19124
(215) 535-7110

General Description:

| System | Description | Label Rating | Design Pressure Rating |
|--------|---|---------------------------------|------------------------|
| 1 | Inspira New Construction Vinyl Casement Windows | Class LC-PG50 36 x 72 Type C | ±50 psf |
| 2 | Inspira Replacement Vinyl Casement Windows | Class LC-PG60 36 x 72 Type C | ±60 psf |

Product Dimensions:

| System | Overall Size | Vent Size |
|--------|--------------|-------------------|
| 1, 2 | 36" x 72" | 34-1/8" x 70-1/8" |

Product Identification (Certification Label on Window):

| System | | | |
|--------|----------------------------------|-------------------------------|--|
| 1 | Certification Agency | Keystone | |
| | Manufacturer's Name or Code Name | 86-725 | |
| | Product Name | Inspira Casement (NC) | |
| | Test Standards | AAMA/WDMA/CSA 101/IS2/A440-11 | |
| 2 | Certification Agency | Keystone | |
| | Manufacturer's Name or Code Name | 86-726 | |
| | Product Name | Inspira Casement (Repl) | |
| | Test Standards | AAMA/WDMA/CSA 101/IS2/A440-11 | |

Impact Resistance:

| System | Impact Resistant | Requirement |
|--------|------------------|---|
| 1, 2 | No | Provide an impact protective system when installing the product in areas that require windborne debris. |

Installation:

| System | | |
|--------|---------------------------|--|
| 1, 2 | Type of Installation | Install the windows in accordance with Drawing TDI-INSPIRA-CA-NI; sheets 1 through 3 of 3; dated February 20, 2020; Revision 0; Signed, sealed, and dated November 17, 2020 by Lucas A. Turner, P.E. |
| | Wall Framing | |
| | Fasteners | |
| | Fastener Location/Spacing | |
| | Fastener Penetration | |

Note: Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.