

Product Evaluation

DR1094 | 0620

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at 800-248-6032.

Evaluation ID: DR-1094

Effective Date: June 1, 2020

Re-evaluation Date: June 2024

Product Name: Prime Wood Fixed Sliding Door Sidelite, Brickmould Installation, Non-Impact Resistant

Manufacturer: Lincoln Wood Products, Inc.

1400 W. Taylor St.

P. O. Box 375

Merrill, WI 54452

(715) 536-2461

General Description:

System	Description	Label Rating	Design Pressure Rating
1	Prime Wood Fixed Sliding Door Sidelite; Narrow Stile	CW-PG50 (50 x 98)-FD	+50 / -50 psf
2	Prime Wood Fixed Sliding Door Sidelite; Lifestyle Stile	CW-PG50 (51 x 110)-FD	+50 / -50 psf
3	Prime Wood Fixed Sliding Door Sidelite; Wide Stile	CW-PG50 (51 x 110)-FD	+50 / -50 psf

Product Dimensions:

System	Overall Size	Fixed Panel Size	Fixed Daylight Opening Size
1	49-5/8" x 98-1/4"	47-1/4" x 95-9/16"	42-1/16" x 89-1/2"
2	49-7/8" x 110-1/4"	47-5/8" x 107-9/16"	40-11/16" x 100-5/8"
3	50-5/8" x 110-1/4"	48-1/4" x 107-9/16"	38-1/2" x 97-3/4"

Product Identification (Certification Label on Door):

System		
1	Certification agency	AAMA
	Manufacturer's name or code name	LN-1
	Product name	WOOD NARROW STILE FIXED SLIDE DOOR
	Test standards	AAMA/WDMA/CSA 101/I.S.2/A440-17
2	Certification agency	AAMA
	Manufacturer's name or code name	LN-1
	Product name	WOOD LIFESTYLE FIXED SLIDE DOOR
	Test standards	AAMA/WDMA/CSA 101/I.S.2/A440-17
3	Certification agency	AAMA
	Manufacturer's name or code name	LN-1
	Product name	WOOD WIDE STILE FIXED SLIDE DOOR
	Test standards	AAMA/WDMA/CSA 101/I.S.2/A440-17

Impact Resistance:

System	Impact Resistant	Requirement
1-3	No	Provide an impact protective system when installing the product in areas that require windborne debris protection.

Installation:

System		
1-3	Type of installation	Brickmould Installation
	Wall framing	Spruce-Pine-Fir dimension lumber
	Fasteners	No. 6 x 2-1/2" screws
	Fastener location/spacing	2"-3" from each corner and 6" on center along the head and side jambs
	Fastener penetration	Minimum of 1-1/2" into the wall framing

Note: Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.