

Product Evaluation

DR1201 | 0921

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at 800-248-6032.

Evaluation ID: DR-1201

Effective Date: September 1, 2021

Re-evaluation Date: September 2025

Product Name: Composite Edge Glazed Fiberglass Side Hinged Entry Doors with Blinds between Glass, Inswing/Outswing, Singles with or without Boxed Sidelites, and Doubles, Impact Resistant

Manufacturer: Therma-Tru Corporation
118 Industrial Dr.
Edgerton, OH 43517
(419) 298-1740

General Description:

System	Description	Label Rating	Drawing Number
1	3'-0" x 6'-8" Single Door; X	Inswing: +50 / -55 psf Outswing: +50 / -50 psf	TX-5224
2	3'-0" x 6'-8" Single Door w/ Boxed Sidelites & Combination Mullions; OX, XO, OXO	Inswing: +50 / -55 psf Outswing: +50 / -50 psf	TX-5225
3	3'-0" x 6'-8" Double Door; XX	Inswing: +50 / -55 psf Outswing: +50 / -50 psf	TX-5226

General Description:

System	Description	Label Rating	Drawing Number
4	3'-0" x 8'-0" Single Door; X	+50 / -50 psf	TX-5227
5	3'-0" x 8'-0" Single Door w/ Boxed Sidelites & Combination Mullions; OX, XO, OXO	+50 / -50 psf	TX-5228
6	3'-0" x 8'-0" Double Door; XX	Inswing: +40 / -45 psf Outswing: +45 / -45 psf	TX-5229

Product Dimensions:

System	Overall Size	Operable Panel Size	Panel Daylight Opening Size
1	37-3/4" x 82"	36" x 79-1/4"	20-15/16" x 62-7/8"
2	115-3/4" x 82"	36" x 79-1/4"	Door & Sidelite: 20-15/16" x 62-7/8"
3	74-1/2" x 82"	36" x 79-1/4"	20-15/16" x 62-7/8"
4	37-3/4" x 98"	36" x 95-1/4"	20-15/16" x 78-7/8"
5	115-3/4" x 98"	36" x 95-1/4"	Door & Sidelite: 20-15/16" x 78-7/8"
6	74-1/2" x 98"	36" x 95-1/4"	20-15/16" x 78-7/8"

Components and Hardware:

System	Component	Quantity	Attachment Method
1-6	Hinges	3 (6'8" doors) 4 (8'0" doors)	Install hardware in accordance with Therma-Tru drawings No. TX-5224 through TX-5229, dated July 21, 2021. Signed and sealed by Lyndon F. Schmidt, P.E. on July 26, 2021.
	Knob: Schlage F51 Deadbolt: Schlage B60 OR Knob: Kwikset Signature Series Deadbolt: Kwikset Signature Series (980)	1 each	
	Latch and deadbolt strike plates	1 each	
	Astragal strike plate (Systems 3, 6)	1	

Product Identification (Manufacturer Label on Door):

System		
1-6	Manufacturer's name or code name	Therma-Tru Corporations
	Product name	Glazed Fiberglass Side Hinged Doors, Inswing/Outswing, Singles & Doubles w/ or w/out Sidelites, Impact Resistant
	Test standards	ASTM E330-14/E1886-13a/E1996-14 Missile Level D

Impact Resistance:

System	Impact Resistant	Requirement
1-6	Yes	These products satisfy TDI's criteria for protection from windborne debris. Install the assemblies at a height on the structure that does not exceed the design pressure rating for the assemblies.

Acceptance of Smaller Assemblies: Door assemblies with dimensions equal to or smaller than those specified are acceptable within the limitations in this report.

Installation:

System		
1-6	Type of installation	Install the assembly in accordance with Therma-Tru drawings No. TX-5224 through TX-5229, dated July 21, 2021. Signed and sealed by Lyndon F. Schmidt, P.E. on July 26, 2021.
	Wall framing	
	Fasteners	
	Fastener location/spacing	
	Fastener penetration	

Note: Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.