

PO Box 149104 | Austin, TX 78714 | 1-800-578-4677 | tdi.texas.gov

Product Evaluation

DR545 | 0620

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at 800-248-6032.

Evaluation ID: DR-545 **Effective Date:** June 1, 2020

Re-evaluation Date: June 2024

Product Name: 8'0" Opaque Fiberglass Side Hinged Doors, Inswing and Outswing, Single with

20 min. Fire Rating, Impact Resistant

Manufacturer: Plastpro, Inc.

5200 W. Century Blvd. Los Angeles, CA 90045

(440) 969-9773

General Description:

System	Description	Label Rating	Drawing Number
1	3'-0" x 8'-0" Single Door (X)	+65 / -65 psf Missile Level D	TX-4149

Product Dimensions:

System	Overall Size	Operable Panel Size
1	Inswing: 37.5" x 98" Outswing: 37.5" x 97.13"	35.75" x 95.25"

Components and Hardware:

System	Component	Quantity	Attachment Method	
	Hinges	4	Install hardware in accordance with	
1	Kwikset Signature Series Passage Lock	1	Plastpro drawing No. TX-4149, dated	
'	Kwikset Signature Series Deadbolt (780)	1	May 9, 2012. Revision 1 dated May 4, 2020. Signed and sealed by Lyndon F.	
	Lock and Deadbolt Strike Plates	1 each	Schmidt, P.E. on May 4, 2020.	

Product Identification (Manufacturer Label on Door):

System		
	Certification agency	Self-labeled
	Manufacturer's name or code name	Plastpro, Inc.
1	Product name	Opaque Fiberglass Side Hinged Doors,
		Inswing/Outswing, Impact Resistant Door
		Panels, Singles
	Test standards	ASTM E330-14/E1886-13a/E1996-14a
		Missile Level D

Impact Resistance:

pact itesis	impact Resistance.		
System	Impact Resistant	Requirement	
1	Yes	These products satisfy TDI's criteria for protection from windborne debris. Install the assemblies at a height on the structure that does not exceed the design pressure rating for the assemblies.	

Installation:

System		
1	Type of installation Wall framing Fasteners	Install in accordance with Plastpro drawing No. TX-4149, dated May 9, 2012. Revision 1 dated May
	Fastener location/spacing Fastener penetration	4, 2020. Signed and sealed by Lyndon F. Schmidt, P.E. on May 4, 2020.

Note: Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.