

PO Box 12030 | Austin, TX 78711 | 800-578-4677 | tdi.texas.gov

Product Evaluation

DR648 | 0521

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at 800-248-6032.

Evaluation ID: DR-648 **Effective Date:** May 1, 2021

Re-evaluation Date: April 2024

Product Name: Glazed Fiberglass Side Hinged Entrance Doors, with Sidelites, Doubles, Inswing,

Impact Resistant

Manufacturer: Nan Ya Plastics Corporation USA

8989 North Loop East Houston, TX 77029 (713) 674-7822

General Description:

| System | Description | Label rating | Design Pressure Rating |
|--------|--|--|---------------------------|
| 1 | Glazed Fiberglass Side Hinged Entrance Doors with Sidelites, Doubles; (OXXO) | R-PG50 (144 x 83)-SHD Missile Level D | +50 / -50 psf |

Component Dimensions:

| System | Overall Size | Panel Size | Maximum Daylight Opening Size |
|--------|--------------------|---|-------------------------------|
| 1 | 143-1/4" x 82-1/2" | <u>Door and Sidelite</u> 34-1/2" x 79-1/8" | 25" x 63" |

Components and Hardware:

| System | Component | Quantity | Attachment Method |
|--------|-----------------------------------|---------------|----------------------------------|
| | 4" Butt Hinges | 3 per panel | |
| | Jam Yuan Enterprieses Co., LTD | 1 per passive | Install hardware in accordance |
| | Top/Bottom Drive Bar system | door panel | with drawing 08-01553, dated |
| | Jam Yuan Enterprieses Co., LTD 2- | 1 per active | May 31, 2012. Revision B dated |
| 1 | point Locking system | door panel | |
| | Jam Yuan Enterprieses Co., LTD | 1 per head | December 19, 2019. Signed and |
| | Head Keeper | frame | sealed by Luis R. Lomas, P.E. on |
| | Jam Yuan Enterprieses Co., LTD | 1 | April 13, 2021. |
| | Sill Keeper | 1 per sill | |

Product identification (Certification Agency Label on Door):

| System | - | |
|--------|----------------------------------|---|
| | Certification agency | NAMI |
| | Manufacturer's name or code name | Nan Ya Plastics USA |
| | Product name | Inswing Hinged Fiberglass Impact Glazed |
| 1 | | Double Door w/ or w/o Sidelites |
| | Test standards | AAMA/WDMA/CSA 101/I.S.2/A440-08 |
| | | ASTM E 1886-05/1996-05 |
| | | Missile Level D |

Impact Resistance:

| | in pact Kesistance. | | |
|--------|---------------------|---|--|
| System | Impact Resistant | Requirement | |
| 1 | Yes | These products satisfy TDI's criteria for protection from windborne debris. Install the assemblies at a height on the structure that does not exceed the design pressure rating for the assemblies. | |

Installation:

| System | | |
|--------|---------------------------|--|
| | Type of installation | |
| | Wall framing | Install in accordance with drawing 08-01553, dated May |
| 1 | Fasteners | 31, 2012. Revision B dated December 19, 2019. Signed |
| | Fastener embedment | and sealed by Luis R. Lomas, P.E. on April 13, 2021. |
| | Fastener location/spacing | |

Note: Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.