

PO Box 149104 | Austin, TX 78714 | 1-800-578-4677 | tdi.texas.gov

Product Evaluation

DR820 | 0823

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at 800-248-6032.

Evaluation ID: DR-820 **Effective Date:** September1, 2023

Re-evaluation Date: March 2026

Product Name: Camelot Vinyl Sliding Glass Doors, Fin and Frame Installation, Non-Impact

Resistant

Manufacturer: Northeast Building Products

4280 Aramingo Ave. Philadelphia, PA 19124

(215) 535-7110

General Description:

System	Description	Label Rating	Design Pressure Rating
1	Camelot Vinyl Sliding Glass Doors (OX, XO)	R-PG25 (96 x 96)-SD	+25 / -25 psf
2	Camelot Vinyl Sliding Glass Doors (OX, XO)	R-PG30 (96 x 96)-SD	+30 / -30 psf
3	Camelot Vinyl Sliding Glass Doors (OX, XO)	R-PG50 (72 x 80)-SD	+50 / -55 psf
4	Camelot Vinyl Sliding Glass Doors (OXO)	R-PG40 (106 x 80)-SD	+40 / -40 psf

Product Dimensions:

System	Overall Size	Operable Panel Size	Fixed Panel Daylight Opening Size
1-2	96" x 96"	48" x 93"	40-1/4" x 85-1/4"
3	71-1/2" x 79-1/2"	35-3/4" x 76-1/2"	28" x 68-3/4"
4	106" x 79-1/2"	35-3/8" x 76-1/2"	27-5/8" x 68-3/4"

Product Identification (Certification Label on Door):

System			
1	Certification agency	Keystone	
	Manufacturer's name or code name	CAR# 86-101	
	Product name Camelot New Construction Slid		
		Door OX	
	Test standards	AAMA/WDMA/CSA 101/I.S.2/A440-11	
2	Certification agency	Keystone	
	Manufacturer's name or code name	CAR# 86-102	
	Product name	Camelot Replacement Sliding Glass Door	
		OX	
	Test standards	AAMA/WDMA/CSA 101/I.S.2/A440-11	
3	Certification agency	Keystone	
	Manufacturer's name or code name	CAR# 86-104	
	Product name	Camelot Sliding Glass Door XO	
	Test standards	AAMA/WDMA/CSA 101/I.S.2/A440-11	
4	Certification agency	Keystone	
	Manufacturer's name or code name	CAR# 86-105	
	Product name	Camelot Sliding Glass Door OXO	
	Test standards	AAMA/WDMA/CSA 101/I.S.2/A440-11	

Impact Resistance:

System	Impact Resistant	Requirement
1-4	No	Provide an impact protective system when installing the product in areas that require windborne debris protection.

Installation:

System		
	Type of installation	Install in accordance with Northeast Building Products
	Wall framing	drawing TDI CAMELOT SGD, titled "Camelot Sliding
1-4	Fasteners	Glass Door OXO", dated December 21, 2015. Revision A
	Fastener location/spacing	dated September 29, 2020. Signed and sealed by Lucas
	Fastener penetration	A. Turner, P.E. on September 29, 2020.

Note: Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.