TDI Texas Department of Insurance

PO Box 12030 | Austin, TX 78711 | 800-578-4677 | tdi.texas.gov

Product Evaluation

DR836 | 1121

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at 800-248-6032.

Evaluation ID: DR-836

Effective Date: November 1, 2021 **Re-evaluation Date:** November 2025

Product Name: Glazed Fiberglass Side Hinged Entry Doors, Inswing and Outswing, Singles and Doubles, with or without Sidelites. Non-Impact Resistant

Manufacturer: HM Sure Rock 15759 Tapia St. Irwindale, CA 91706 (626) 214-0833

General Description:

System	tem Description Label Rating		Drawing Number
1	3'-0" x 6'-8" Single Door; X	+45 / -45 psf	TX-4821
2	3'-0" x 6'-8" Single Door w/ Boxed Sidelite & Combination Reinforced (2X) Mullion; +45 / -45 psf TX-482 XO, XO		TX-4822
3'-0" x 6'-8" Single Door w/ Boxed Sidelites & Combination Reinforced (2X) Mullions; +45 / -45 psf OXO		TX-4822	
4 6'-0" x 6'-8" Double Door; XX		+45 / -45 psf	TX-4823

System	Description	Label Rating	Drawing Number
5	6'-0" x 6'-8" Double Door w/ Boxed Sidelites & Combination Mullion; OXXO	+40 / -40 psf	TX-4823
6 6'-0" x 6'-8" Double Door w/ Boxed 5 Sidelites & Combination Reinforced (1X) +45 / -45 psf Mullions; OXXO		TX-4823	
6'-0" x 6'-8" Double Door w/ Boxed7Sidelites & Combination Reinforced (2X) Mullions; OXXO		TX-4823	

General Description:

Product Dimensions:

System	Overall Size	Operable Panel Size	Panel Daylight Opening Size
1	37-3/4" x 81-3/4"	35-3/4" x 79"	Door: 20-7/8" x 62-7/8" Sidelite: N/A
2	52-1/2" x 81-3/4"	35-3/4" x 79"	Door: 20-7/8" x 62-7/8" Sidelite: 5-7/8" x 62-7/8"
3	67-1/2" x 81-3/4"	35-3/4" x 79"	Door: 20-7/8" x 62-7/8" Sidelite: 5-7/8" x 62-7/8"
4	74" x 81-3/4"	35-3/4" x 79"	Door: 20-7/8" x 62-7/8" Sidelite: N/A
5-7	104" x 81-3/4"	35-3/4" x 79"	Door: 20-7/8" x 62-7/8" Sidelite: 5-7/8" x 62-7/8"

Components and Hardware:

System	Component	Quantity	Attachment Method
	Hinges	3	
1-4	Knob: Kwikset Signature Series Deadbolt: Kwikset Signature Series (980) OR Knob: Schlage F Series (F51) Deadbolt: Schlage B Series (B60N)	1 each	Install hardware in accordance with drawing No. TX-4821 through TX-4823, dated July 25, 2016. Revision 1 dated September 23, 2021. Signed and sealed by Lyndon F. Schmidt, P.E. on
	Latch and Deadbolt strike plate	1 each	September 23, 2021.
	Astragal strike plate (Systems 4-7)	1	

S	ystem		
		Manufacturer's name or code name	HM Sure Rock
			Glazed Fiberglass Side Hinged Doors,
	1-7	Product name	Inswing/Outswing, Singles & Doubles w/
			or w/out Sidelites, Non-Impact Resistant
		Test standards	ASTM E330-14

Product Identification (Manufacturer Label on Door):

Impact Resistance:

System	Impact Resistant	Requirement
1-7	No	Provide an impact protective system when installing the product in areas that require windborne debris.

Acceptance of Smaller Assemblies: Door assemblies with dimensions equal to or smaller than those specified are acceptable within the limitations specified in this report.

Installation:

System		
1-7	Type of installation Wall framing Fasteners Fastener location/spacing	Install in accordance with drawing No. TX-4821 through TX-4823, dated July 25, 2016. Revision 1 dated September 23, 2021. Signed and sealed by Lyndon F. Schmidt, P.E. on September 23, 2021.
	Fastener penetration	,

Note: Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.