

## **Direct Wood Mounting Detail**


Bracket Mount Shown, Reverse and Continuous Angle Mount Also Approved As Alternate.

439 lbs. per anchor allowable load 5/16" Dia. Lag Screw w/1-1/8" O.D. Flat Washer (shall conform to ANSI/ASME standard B18.2.1)

Minimum Screw Length: Spruce-Pine-Fur (SPF) - 2-1/2" Southern Pine - 1-5/8"

Minimum Edge Distance: 1/2" Maximum on Center Spacing: 24"

D




# **Direct Concrete Mounting Detail**

Continuous Angle Clip Mount Shown, Bracket and Reverse Continuous Angle Mount Also Approved As Alternate.

831 lbs. per anchor allowable load 3/8" Dia. Ankr-Tite CCAT w/1-1/8" O.D. Flat Washer (by Wej-It Fastening Systems) Minimum Embedment: 2-5/8" Minimum Edge Distance: 2-1/2"

Minimum on Center Spacing: 6" Maximum on Center Spacing: 24"




### **Direct Steel Mounting Detail**

Bracket Mount Shown, Reverse and Continuous Angle Mount Also Approved As Alternate.

232 lbs. per anchor allowable load - 12 Ga Ste569el lbs. per anchor allowable load -  $\frac{3}{16}$ " Ga Steel 5/16"-12 Tek Self-Drilling Screw w/9/16" O.D. Flat Washer


12 Ga Maximum on Center Spacing: 24" 3 Maximum on Center Spacing: 24"



### **Direct Concrete Mounting Detail**

Continuous Angle Clip Mount Shown, Bracket and Reverse Continuous Angle Mount Also Approved As Alternate.

562 lbs. per anchor allowable load 1/4" Dia. Concrete Self-Tapping & Wedge Anchor w/1" O.D. Flat Washer (Includes Tapcon+ (by ITW), Wedge-Bolt+ (by Powers Fasteners) & Red Head TruBolt wedge anchor (by ITW)) Minimum Embedment: 2" Minimum Edge Distance: 2-1/2" Minimum on Center Spacing: 5" Maximum on Center Spacing: 24"



# **Direct Steel Mounting Detail**

Reverse Continuous Angle Clip Mount Shown, Continuous Angle Mount Also Approved As Alternate.

1272 lbs. per anchor allowable load 1/8" Nom. x 1" Long Fillet and 1/4" Long Tack Weld (E60xx Electrodes Min.)

Welds performed by a certified welder or inspected by a certified welding inspector to verify integrity of the welds.

Maximum on Center Spacing: Apply welds at each roller location not to exceed 24"

> John E Scates, P.E. 2560 King Arthur Blvd. Ste 124-54 Lewisville, Texas 75056 Texas P.E. 56308/F2203

Professional Engineer seal provided only for verification of wind load construction details.



#### **DESCRIPTION:** 9' 2" HT 600, 700, 2000, 800 & 900/9000 AMERICAN TRADITION SERIES W/LITES WIND LOAD SECTIONAL DOOR

DESIGN PRESSURE +21.3/-24.1 PSF DRAWING NO.: WLT-0600-0110-08-21-24L | REV. A

SHEET: 4 OF 4

**DRAWN BY:** MVS | **DATE DRAWN:** 10/23/18 | **REV. DATE:** 3/2/22 **MODEL(S):** See Sheet 3

2 6 8