

PO Box 149104 | Austin, TX 78714 | 1-800-578-4677 | tdi.texas.gov

Product Evaluation

WIN1596 | 0920

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at (800) 248-6032.

Evaluation ID: WIN-1596 **Effective Date:** September 1, 2020

Re-evaluation Date: February 2023

Product Name: Impervia Fiberglass Vent Awning Windows, Non-Impact Resistant

Manufacturer: Pella Corporation

102 Main St. Pella, IA 50219 (641) 621-1000

General Description:

System	Description	Label Rating	Design Pressure Rating
1	Impervia Fiberglass Large Vent Awning Windows	LC-PG30 (60 x 42)-AP	+30 / -30 psf
2	Impervia Fiberglass Large Vent Awning Windows	LC-PG30 (60 x 60)-AP	+30 / -30 psf
3	Impervia Fiberglass Vent Awning Windows	LC-PG50 (54 x 30)-AP	+50 / -50 psf
4	Impervia Fiberglass Large Vent Awning Windows	LC-PG50 (42 x 42)-AP	+50 / -50 psf
5	Impervia Fiberglass Large Vent Awning Windows	LC-PG50 (42 x 60)-AP	+50 / -50 psf
6	Impervia Fiberglass Vent Awning Windows	LC-PG50 (28 x 30)-AP	+50 / -50 psf

Product Dimensions:

System	Overall Size	Operable Sash Size
1	59-1/2" x 41-1/2"	56-15/16" x 38-15/16"
2	59-1/2" x 59-1/2"	56-15/16" x 56-15/16"
3	53-1/2" x 29-1/2"	50-15/16" x 26-15/16"
4	41-1/2" x 41-1/2"	38-15/16" x 38-15/16"
5	41-1/2" x 59-1/2"	38-15/16" x 56-15/16"
6	27-1/2" x 29-1/2"	24-15/16" x 26-15/16"

Product Identification (Certification Label on Window):

System	•	,
	Certification Agency	WDMA
1-2, 4-5	Manufacturer's Name or Code Name	Pella Corporation
1-2, 4-5	Product Name	Impervia Large Vent Awning
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-08,11
	Certification Agency	WDMA
2.6	Manufacturer's Name or Code Name	Pella Corporation
3, 6	Product Name	Impervia Vent Awning
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-08,11

Impact Resistance:

System	Impact Resistant	Requirement
1-6	No	Provide an impact protective system when installing the product in areas that require windborne debris protection.

Installation:

System		
	Type of Installation	lookelli is a see oden see iith Bella Camanatian
	Wall Framing	Install in accordance with Pella Corporation
1-6	Fasteners	drawing No. 1676T, dated July 8, 2014. Revision A1 dated January 28, 2019. Signed and sealed by
	Fastener Location/Spacing	Warren W. Schaefer, P.E. on July 17, 2020.
	Fastener Penetration	Walter W. Schaeler, F.E. Off July 17, 2020.

Note: Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.