

PO Box 149104 | Austin, TX 78714 | 1-800-578-4677 | tdi.texas.gov

# **Product Evaluation**

#### WIN1597 | 0920

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at (800) 248-6032.

Evaluation ID: WIN-1597

Effective Date:September 1, 2020Re-evaluation Date:December 2022

Product Name: Impervia Fiberglass Vent Casement Windows, Non-Impact Resistant

Manufacturer: Pella Corporation 102 Main St. Pella, IA 50219 (641) 621-1000

#### **General Description:**

System	Description	Label Rating	Design Pressure Rating
1	Impervia Fiberglass Vent Casement Windows	LC-PG50 (32 x 72)-C	+50 / -50 psf
2	Impervia Fiberglass Vent Casement Windows	LC-PG50 (38 x 28)-C	+50 / -50 psf
3	Impervia Fiberglass Vent Casement Windows	LC-PG50 (38 x 72)-C	+50 / -50 psf
4	Impervia Fiberglass Vent Casement Windows	LC-PG50 (38 x 80)-C	+50 / -50 psf

#### **Product Dimensions:**

System	Overall Size	Operable Sash Size
1	32" x 72-1/4"	29-7/16" x 69-11/16"
2	37-1/2" x 27-1/2"	34-15/16" x 24-15/16"
3	37-1/2" x 72-1/4"	34-15/16" x 69-11/16"
4	37-1/2" x 79-1/2"	34-15/16" x 76-15/16"

## Product Identification (Certification Label on Window):

System		
1-4	Certification Agency	WDMA
	Manufacturer's Name or Code Name	Pella Corporation
	Product Name	Impervia Vent Casement
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11

#### Impact Resistance:

System	Impact Resistant	Requirement
1-4		Provide an impact protective system when installing the product in areas that require windborne debris protection.

### Installation:

System		
	Type of Installation	
	Wall Framing	Install in accordance with Pella Corporation
1-4	Fasteners	drawing No. 1675T, dated July 8, 2014. Revision A1 dated January 28, 2019. Signed and sealed by
	Fastener Location/Spacing	Warren W. Schaefer, P.E. on July 17, 2020.
	Fastener Penetration	Warren W. Schaeler, P.E. Off July 17, 2020.

**Note:** Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.