

PO Box 12030 | Austin, TX 78711 | 800-578-4677 | tdi.texas.gov

# **Product Evaluation**

WIN1802 | 0622

**Engineering Services Program** 

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at (800) 248-6032.

**Evaluation ID:** WIN-1802 **Effective Date:** June 1, 2022

**Re-evaluation Date:** January 2026

Product Name: Series 142.000/143.000/145.000 Vinyl Picture Windows, Fin and Frame

Installation, Impact Resistant

Manufacturer: Showcase Windows and Doors

12613 Citypark Dr. Unit 100 Missouri City, TX 77489

(713) 926-8500

#### **General Description:**

| System | Description   | Label Rating                                  | Design Pressure<br>Rating |
|--------|---|---|---------------------------|
| 1      | Series 142.000/143.000/145.000<br>Vinyl Picture Windows | FW-C80 (64 x 84)<br>Missile Level D           | +50 / -50 psf             |
| 2      | Series 142.000/143.000/145.000<br>Vinyl Picture Windows | FW-C80 (50 x 63)<br>Missile Level D (48 x 60) | +60 / -60 psf             |

#### **Product Dimensions:**

| System | Overall Size | Fixed Sash Daylight Opening Size |  |
|--------|--------------|----------------------------------|--|
| 1      | 64" x 84"    | 59" x 79"                        |  |
| 2      | 48" x 60"    | 43" x 55"                        |  |

## **Product Identification (Certification Label on Window):**

| System |                                     |  |
|--------|-------------------------------------|--|
| 1      | Certification Agency                | Keystone                                 |
|        | Manufacturer's Name or<br>Code Name | CAR# 839-1040 / 839-214                  |
|        | Product Name                        | 142.000/143.000/145.000NC/Rep Imp Fixed  |
|        | Test Standards                      | AAMA/WDMA/CSA 101/I.S.2/A440-05          |
|        |                                     | ASTM E1886-05/E1996-06                   |
|        |                                     | Missile Level D                          |
| 2      | Certification Agency                | Keystone                                 |
|        | Manufacturer's Name or<br>Code Name | CAR# 839-1041 / 839-226                  |
|        | Product Name                        | 142.000/143.000/145.000 NC/Rep Imp Fixed |
|        |                                     | AAMA/WDMA/CSA 101/I.S.2/A440-05          |
|        | Test Standards                      | ASTM E1886-05/E1996-09                   |
|        |                                     | Missile Level D                          |

#### **Impact Resistance:**

| System | Impact Resistant | Requirement   |
|--------|------------------|---|
| 1-2    | Yes              | These products satisfy TDI's criteria for protection from windborne debris. Install the assemblies at a height on the structure that does not exceed the design pressure rating for the assemblies. |

## Installation:

| System |                           |  |  |
|--------|---------------------------|--|--|
| 1      | Type of Installation      | Install in accordance with drawing No. 08-03106, dated April 26, 2017. Revision A dated December 14, 2021. Signed and sealed by Luis R. Lomas, P.E. on February 2, 2022. |  |
|        | Wall Framing              |  |  |
|        | Fasteners                 |  |  |
|        | Fastener Location/Spacing |  |  |
|        | Fastener Penetration      |  |  |
| 2      | Type of Installation      | Frame Installation   |  |
|        | Wall Framing              | Spruce-Pine-Fir dimension lumber   |  |
|        | Fasteners                 | No. 8 PPH screws   |  |
|        | Fastener Location/Spacing | Head/Sill: 6", 20", 30", and 44" measuring from the  |  |
|        |                           | left side jamb.  |  |
|        |                           | Side jambs: 6", 20", 32", 44", and 57" measuring   |  |
|        |                           | from the head jamb   |  |
|        | Fastener Penetration      | Minimum of 1-1/2" into the wall framing  |  |

**Note:** Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.