

TEXAS DEPARTMENT OF INSURANCE

Engineering Services Program / MC 103-3A 333 Guadalupe Street P.O. Box 149104 Austin, Texas 78714-9104
Phone No. (512) 322-2212 Fax No. (512) 463-6693

PRODUCT EVALUATION

WIN-1762

Effective Date: July 1, 2013 (Revised June 1, 2014)

Reevaluation Date: **July 2016**

The following product has been evaluated for compliance with the wind loads specified in the **International Residential Code (IRC)** and the **International Building Code (IBC)**.

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

Series 8800 Vinyl Casement Windows, Replacement Construction, Impact Resistant, manufactured by

Wincore Windows and Doors
250 Staunton Turnpike
Parkersburg, WV 26104
Telephone: (304) 485-7460

General Description:

System	Description	Label Rating	Design Pressure Rating
1	Series 8800 Vinyl Casement Window; (X)	LC-PG50 36 x 72-C Missile Level D	± 50 psf
2	Series 8800 Vinyl Casement Window; (X)	LC-PG65 36 x 72-C Missile Level D	+65 / -70 psf
3	Series 8800 Vinyl Casement Window; (X)	LC-PG55 36 x 72-C Missile Level D	+55 / -55 psf

Product Dimensions:

System	Overall Size	Sash Size
1	36.00" x 72.00"	34.62" x 70.62"
2	36.00" x 72.00"	34.62" x 70.62"
3	36.00" x 72.00"	34.62" x 70.62"

Product Identification (Certification Agency Label on Window):

System	Certification Agency	NAMI
1, 2, 3	Manufacturer's Name or Code Name	Wincore Window Company, LLC
	Product Name	8800 Series Impact Vinyl Out-Swing Casement Window
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-08; ASTM E 1886-05; ASTM E 1996-06; Wind Zone 4; Missile Level D

Impact Resistance:

Impact Resistant	Requirement
Yes	These products satisfy the Texas Department of Insurance's criteria for protection from windborne debris in the Inland I and Seaward zone . The assemblies may be installed at any height on the structure as long as the design pressure rating for the assemblies is not exceeded.

Installation:

General: The window assembly shall be prepared and installed in accordance with the manufacturer's recommended installation instructions, the approved drawings referenced below, and this evaluation report. Detailed installation instructions and component drawings are available from the manufacturer.

Design Drawings: The windows shall be installed in accordance with Drawing No. TX-4243, titled "Wincore Windows & Doors 8800 Series Vinyl Outswing Casement Window 'Impact'," sheets 1 through 4 of 4, dated September 10, 2012, Rev 1., dated August 27, 2013, signed and sealed by Lyndon F. Schmidt, P.E on August 27, 2013. The stated drawings will be referred to as the approved drawings in this evaluation report.

Installation: The windows shall be installed as specified on Sheets 1 of 4 through 4 of 4 of the approved drawings.

Note: The manufacturer's installation instructions shall be available on the job site during installation. All fasteners shall be corrosion resistant as specified in the International Residential Code (IRC), the International Building Code (IBC), and the Texas Revisions.